

TICOUIT INO.	DESCRIPTION		Commencing (C) 501		MODIFICATIONS		
			Illus. No.		New Part Number	Change Point	REMARKS
	INSTRUMENTS						
2	Speedometer (miles) Speedometer (kilos)	17H292	1				
5	Bezel	<b>17H293</b> N.S.P.	2	1			
	Strap	AJH5176	3				Was 27H397
	Glass Ring—(rubber)	N.S.P.	4				
	Knob—trip	AJH5178 AJH5179	5				
	Washer (spring)	27H387	7			-	
	Nut (knurled) Bulb—speedometer illumination	17H932	8				
1 .	Bulb—beam warning light	BFS987 BFS987	9				Part No. change was 2H4732
S 10 30		37H5181	10	12			Part No. change was 2H4732
	Sleeve (rubber)	ACG5185	10				
,	Cable—speedometer (5′ 3″ [160·02 cm])	27H1393		1		7 Fin. (C) 712 LHD	27H1393 not available
	Cable (inner)	17111040	2.7			Fin. (C) 712 LHD Fin. (C) 2466	use BCA4079
	Cable (inner)	17H1346 27H1391	11		-	RHD	
(	Cable—speedometer (5' 3" [160·02 cm])	27111001	12		BCA4079	-	
	Cable (unner) Cable (outer)				17H1346	Com. (C) 2467	
(	Cable—speedometer (5′ 6″ [167:64cm])			1	17H1586	1	
	Cable—inner LHD		-	1 1	ACC8788 17H756	Com. (C) 713	
1	Cable—outer			1	17H757	Com. (c) 713	
9	Clip—fixing cable Sleeve for clip (rubber)	PCR0709	13	I		-	
		ACH8529 FNZ104	14	1		-	
I	Vasher for nut (spring)  Grommet—cable—through dash  Grommet—blanking—cable hole in dash  Revolution Counter	LWZ204	16	1			
	rommet—cable—through dash	ACB8474	17	1			
F	Revolution Counter	4G2541	18	1			
	Bezel	BHA4083 N.S.P.	19	11			
	Strap	27H429	21	1			Was 27H397
	Glass Ring (rubber)	N.S.P.	22	1	*****		Was A JH5177
	Washer (shakeproof)	AJH5178	23	1			
	Nut (knurled)	17H1341 17H1304	24	2			
E	outo-levolution confirer illimination	BFS987	26	1			Post No. shanss OTIATOO
	Bulbholder Sieeve (rubber)	37H5181	27	1			Part No. change was 2H4732
В	ould—lgnition warning light	ACG5185		1			
1 1	outpholder	BFS987 47H5166	31	1			Part No. change was 2H4732
	Sleeve (rubber)	ACG5185	33	1	***************************************		
							· · · · · · · · · · · · · · · · · · ·
·····							

DESCRIPTION		Commencing (C) 501		MODIFICATIONS		
	Part Number	Illus. No.	Qty. per Veh.	New Part Number	Change Point	REMARKS
Instruments—continued Cable—revolution counter (48" [121·92cm.]) Cable (inner) Cable (outer) Cable—revolution counter (38" [96·52 cm.]) Cable (inner)  LHI	17H1343 27H1801 27H1860	28 29	1			
Cable (outer)  Grommet—cable—through dash  Grommet—blanking—cable hole in dash	27H1861 ACB8474 4G2541	30	1 1			
Gauge—oil and temperature (farenheit).  Gauge—oil and temperature (centigrade)  Bezel	1711236	35	1 1 1	ВНА4110	Com. (C) 713	Was AJH5182 Was 17H1068
Glass  Ding (rubbar)	N.S.P. 17H1821	37	1 1 1		Com. (C) 713	7 Centigrade gauge
Ring (rubber) Ring (rubber) Strip—window. Strap	A TH5186	39	112	. 17H1481	Com. (C) 713 Com. (C) 713	1
Washer (spring) Nut (knurled) Nut poll and temperature gauge illumination	27H387 17H932 BFS987	40 41 42	2			Part No. change was 2H4732 Correction was 3H914
Bulbholder	ACG5185	43	11 11			
Pipe assembly—oil gauge Pipe—connector to engine (flexible) Washer—oil pipe to oil gauge (leather)	AHH5820 2K4936 83875	45	1			
Connector—on gauge pipe Screw—connector to starter bracket	HZS0406 LNZ104	4748				Alternatives
Nut for screw (nyloc) Washer for screw Grommet—oil gauge pipe	84138	49	11			
Clip—oil gauge pipe to bulkhead (front) Clip—oil gauge pipe to bulkhead (rear) Clip—thermometer pipe to bulkhead (front and rear) Screw—oil and thermometer pipe clip	PCR0207 PCR0307 PCR0307	52	12			
Nut for screw	T W 7903	54 55	2 22			
Clip—thermometer pipe Retainer—clip Courte fuel	AHH5802 17H299	56 57 58	1 11			Was A I H 5182
Glass	N.S.P.	59 60	1			Was AJH5182 Was 17H1068
Ring (rubber) Strap Washer (spring)	AJH5185 27H387	62 63	11			
Nut (knurled)  Bulb—fuel gauge illumination	BFS987 37H5181	65	1			Part No. change was 2H473 Correction was 3H914
Sleeve (rubber)	ACG5185		1			